

sendEmail

1 O que é?

Script que envia email pelo terminal

2 Créditos

sendEmail-1.56 by Brandon Zehm caspien@dotconf.net

3 Instalação

```
sudo apt-get install sendmail
```

3 Sintaxe

```
sendEmail -f ADDRESS [options]
```

4 Instruções (ManPage)

Aqui há uma reprodução do comando sendmail --help.

Required:

- -f ADDRESS - from (sender) email address
- At least one recipient required via -t, -cc, or -bcc
- Message body required via -m, STDIN, or -o message-file=FILE

Common:

- -t ADDRESS [ADDR ...] to email address(es)
- -u SUBJECT message subject
- -m MESSAGE message body
- -s SERVER[:PORT] smtp mail relay, default is localhost:25
- -S [SENDMAIL_PATH] use local sendmail utility (default: /usr/bin/sendmail) instead of network MTA

Optional:

- -a FILE [FILE ...] file attachment(s)
- -cc ADDRESS [ADDR ...] cc email address(es)
- -bcc ADDRESS [ADDR ...] bcc email address(es)
- -xu USERNAME username for SMTP authentication
- -xp PASSWORD password for SMTP authentication

Paranormal:

- -b BINDADDR[:PORT] local host bind address
- -l LOGFILE log to the specified file
- -v verbosity, use multiple times for greater effect
- -q be quiet (i.e. no STDOUT output)
- -o NAME=VALUE advanced options, for details try: --help misc
 - -o message-content-type=<auto|text|html>

- -o message-file=FILE -o message-format=raw
- -o message-header=HEADER -o message-charset=CHARSET
- -o reply-to=ADDRESS -o timeout=SECONDS
- -o username=USERNAME -o password=PASSWORD
- -o tls=<auto|yes|no> -o fqdn=FQDN

Help:

- --help the helpful overview you're reading now
- --help addressing explain addressing and related options
- --help message explain message body input and related options
- --help networking explain -s, -b, etc
- --help output explain logging and other output options
- --help misc explain -o options, TLS, SMTP auth, and more

Fontes

- <https://www.vivaolinux.com.br/artigo/Enviando-emails-pelo-terminal>